



目地部



種類	呼び名	寸法 (mm)													鉄筋						参考重量 (kg)
															横鉄筋				縦鉄筋		
															外側鉄筋		底版内側鉄筋				
		a	b	c	d	d'	e	f	h	t	t'	r	L	径	本数		径	本数		径	
1種	250	250	230	250	40	55	55	55	20	90	50	1000 or 2000	4.0	10	6	-	-	-	4.0	11	290
	300A	300	280	300			60	60		120										13	348
	300B	300	270	400			65	65		95										15	420
	300C	300	260	500			70	70		110										135	14
	400A	400	370	400	45	60	65	65	125	150	5.0	-	-	-	4.0	16	536				
	400B	400	360	500			70	70								17	594				
	500A	500	460	500			75	75								21	680				
	500B	500	450	600			75	75								21	680				
3種	250	250	230	250	45	55	65	65	30	90	120	50	1000 or 2000	5.0	20	10	5.0	20	10	13	333
	300A	300	280	300	70		70	95	24	12	24				12	15	419				
	300B	300	270	400	50		80	80	19	10	10				5	17	585				
	300C	300	260	500	80		80	11	11	11	6				17	516					
	400A	400	370	400	55	70	70	40	110	140	50	D6	23	12	D6	12	6	4.0	19	634	
	400B	400	360	500	80	80	125	155	20										700		
	500A	500	460	500	90	90	175	175	13										7	24	849
	500B	500	450	600	60	60	125	155	13										7	24	849
寸法の許容差		±3					-	±3	-	±6	-										

会社名	図面名称	製図年月日	製図	照査
 (株)桑原コンクリート工業	落ちふた式U型側溝			