



寸法表

種類	呼び名	寸法 (mm)								配筋				参考重量 (kg)										
		b	b ₁	t	t ₁	t ₂	L	r	b ₂	縦鉄筋		横鉄筋												
										径又は呼び名	数量 (本)	径又は呼び名	数量 (本)											
										L = 500	L = 600													
1種	150	210	35	35	30	5	500 又は 600	15	75	2.6	3	2.6	5	5	10									
	180	250	40	40	35				90	3.2	4			3.2	6	13								
	240	330	50	45	40				100							4.0	5	5.0	21					
	300	400	55	60	50	10		18	120	5	D 6	6		34										
	360	460		65	55				150					6	D 6	5	54							
	450	560	60	70	60				180	6	D 6					6	77							
	600	740	75	75	65	20		18	150			6		D 13	6	6	153							
許容差		±3	±2		-	±3	-			-														
2種	150	210	35	90	80	10	500 又は 600	15	75	D 6	3	D 6	7	7	25									
	180	250	40		100	85			15		90	5	D 10	5	5	5	5	30						
	240	330	50	55		150			20		100								6	D 10	6	6	6	6
	300	400	100		85			15		18	120	7	D 10	7	7	7	92							
	360	460																120						
	450	560	60	120	100	20		18	150	6	D 13	6	6	153										
	600	740	75	150	130	20									18	150	6	D 13	6	6	153			
許容差		±3	±2		-	±3	-		-															

*240は両手掛け、300は片手掛けになります。

会社名	図面名称	製図年月日	製図	照査
正 (株) 桑原コンクリート工業	U型側溝 ふた 1種 2種			