



※参考重量 L=2Mの場合

種類	呼び名	※弊社製造品※	寸法 (mm)													鉄筋						参考重量 (kg)															
			a	b	c	d	d'	e	f	h	t	t'	r	L	外側鉄筋		底版内側鉄筋			縦鉄筋																	
															径	本数		径	本数		径		本数														
																1m	2m		1m	2m				1m	2m												
1種	250	-	250	230	250	40	55	55	55	20	90	120	50	1000 or 2000	4.0	10	6	-	-	-	4.0	11	290														
	300A	※L=2M		280	300			60	60																										13	420	
	300B	-	300	270	400			70	70															95												15	497
	300C	-		260	500			65	65															70												14	457
	400A	-		370	400	65	65				110	135											16	536													
	400B	-	400	360	500	70	70				125	150											17	594													
	500A	-	500	460		45	60				75	75											21	680													
	500B	-		450	600	75	75																														
3種	250	※L=2M	250	230	250	45	55	65	65	30	90	120	50	1000 or 2000	5.0	20	10	5.0	20	10	4.0	13	333														
	300A	※L=1M, 2M		280	300			70	70								95														15	472					
	300B	※L=2M	300	270	400			80	80								140														17	585					
	300C	※L=2M		260	500			70	70								110														19	634					
	400A	-		370	400	55					80	80											20	700													
	400B	-	400	360	500	80	80				125	155											24	849													
	500A	-	500	460		60	60				90	90																									
	500B	-		450	600	90	90				125	175																									
寸法の許容差			±3													-		±3		-		±6		-													

会社名	図面名称	製図年月日	製図	照査
(株)桑原コンクリート工業	落ちふた式U形側溝			